

## ADDITIVES, CLEANERS AND REMOVERS

### EPOXY SOLVENT



- Blend of solvents specifically designed to help loosen epoxy Chattanooga stones for easier removal.
- For best results, cover deck with plastic to prevent the evaporation of solvent. Leave covered 4-6 hours then use a chipping hammer to remove softened epoxy.

Item: #204111	1 gal. \$16.10 ea.
#204110	5 gal. \$78.99 ea.

### TOLUENE



- Toluene is used to thin two-part epoxy when using it as a sealer over epoxy Chattanooga.
- Surface must be **COMPLETELY** dry prior to use.

Item: #204132	1 qt. \$6.59 ea.
#204131	1 gal. \$18.99 ea.
#204130	5 gal. \$93.99 ea.

### SOLVENT TG



- Blend of mineral spirits and toluene used for wiping the trowel when installing epoxy bonded stone systems.
- Used to clean solvent based chemicals from the inside of stainless steel and galvanized pump up sprayers.

Item: #204122	1 qt. \$4.99 ea.
#204121	1 gal. \$14.49 ea.
#204120	5 gal. \$59.99 ea.

### WHITE X



- For use on pavers and epoxy Chattanooga that have whitening due to moisture present at the time they were sealed.
- After pressure cleaning, wait 2-3 days for the surface, and the slab or sand underneath the surface, to be **COMPLETELY** dry. Several applications may be required.

Item: #204141	1 gal. \$20.50 ea.
#204140	5 gal. \$85.00 ea.