

2000 Banks Road • Margate, Florida 33063
Decorative Concrete • Products & Systems



PATCH KIT INSTRUCTIONS

Natural Stone - Chattahoochee



Repair Kit Rock

7 Lbs. Container
Covers approx 2-3 sq. ft.
($\frac{3}{8}$ " to $\frac{1}{2}$ " thickness)

Repair Kit Resin/Cure

Provides enough Epoxy to mix 7 Lbs. of Repair Kit Rock.

1. Make sure the surface to be repaired is clean and dry.
2. Mix all of part A (Resin) with all part B (Cure) thoroughly for three to five minutes.
3. Mix the epoxy with the rock provided, making sure each stone is covered with the epoxy.
Approximate 15 to 20 minutes pot life after mixing.
4. Place the rock in the areas to be repaired. Using a trowel or similar tool, smooth the rocks as flat as possible to the adjoining surfaces, wiping your trowel each time with Solvent TG.
5. Allow eight hours to dry.
6. The rock and epoxy provided will cover approximately 1½ to 2 sq. ft. based on $\frac{3}{8}$ " to $\frac{1}{2}$ " thickness.

Natural Stone surface should be sealed every 10 to 12 months with Rock Glaze Sealer.

- Urethane clear coating
- Resists ultraviolet rays



1 Gallon

5 Gallon



Solvent TG

Blend of mineral spirits and toluene. Used for wiping the trowel when installing epoxy stone. Otherwise, the epoxy will stick to the trowel.

Advanced Surfacing Systems

Pool Decks • Patios • Driveways • Walkways • Entranceways



Maintain The
Beauty Of Your
Surface



**ADVANCED
SURFACES**
INC.
Since 1979

Showroom • Warehouse • Office
2000 Banks Road • Margate, FL 33063
Local: 954-973-4528
Out Of Area: 800-952-5980
Fax: 954-973-4926

Visit Us: www.advancedsurfaces.com
Email: sales@advancedsurfaces.com